

Multi-line punching patterns		Machines														
Multi-line punching patterns	Patterns	Punch3300	Punch3400	Punch5000	DocuPunch	AlphaDoc	CoverPunch	EPX700	EX Serie	EM Serie	WIL420SP & MP	CF-SFL390MP	DCR400	Onglematic	EMT 650	Other brands
Combined with 2 perforation lines : Wire-O® or spiral & Tear-off perforation				X				X	X	X						D
Combined with 3 perforation lines : Wire-O® or spiral, Tear-off & ring binder holes								X	X	X						D

Main punching specifications for multi-line patterns

	Max number of lines	Max punching depth		Margin (sheet edge to hole edge)	
		(S)	(M)	Mini	Maxi
PB3300	1	10mm		0	16mm-S
P3400	1	7mm		Marges pré-définies sélectables 2mm 2,5mm 3mm 3,5mm 4,8mm	
P5000	1	10mm		0	24,5mm-S
	2	21,5mm		0	27,3mm-S
Docu-Punch	2	16,5mm		2mm	17mm-S
				0	18,5mm-S
Alpha-Doc	2	18,5mm		0	18,5mm-S
				0	45mm-S
EPX Pour les outils type EX, voir EX	3	29mm		0	45mm-S
				0	45mm-S
EX	3	Simple action	Double action	Ø	2,5mm
		35mm	53mm	□	3mm
EM	3	55mm		50mm-S	
				Ø	2,5mm
				□	3mm
				200mm-S	

